



110V ELECTRIC AIRDECK INFLATOR/ 220V ELECTRIC AIRDECK INFLATOR

PRODUCT NO: SS1101AD (110V) / SS1103AD (220V)

PRODUCT DESCRIPTION:

Air Pressure : 5.7 kPa
Maximum air volume: 4.1 m³/ minute
No load speed: 16.000 min
Overall length: 479mm
Net weight: 2.0kg
Vibration emission: (ah) 2.5m/s²
Sound level: (Lwa) 94dB
Power source: 110v 50-60Hz/220v-240v 50Hz

MATERIAL SPECIFICATION:

Double insulated plastic casing
Copper wire
EPDM Rubber inflation and suction nozzle

OPERATING AND DESIGN STANDARDS:

Conforms to 2006/42/EC
Manufactured to EN60745
Vibration determined to EN60745
Weight according to EPTA 01/2003

INSPECTION ROUTINE:

Before each work session

Always be sure the tool is switched off and unplugged before inspection is performed.
Visually inspect cable and plug connection.



MAINTENANCE SCHEDULE:

Every 3 months

Keep all parts clean and dust free.
Do not use any solvents to clean only a dry rag.

PAT testing to be carried out by authorised and competent person.

Spare parts available from Sayfa Systems.

TRAINING REQUIREMENTS:

All operatives must be trained and wear appropriate PPE including gloves, goggles and ear protection.

Sayfa Systems offer product training and operator certification.