



# 4 STROKE PETROL AIRDECK INFLATOR

PRODUCT NO: SS2501AD

## PRODUCT DESCRIPTION:

Air Pressure : 7.3 kPa  
Maximum air volume: 4.8 m<sup>3</sup>/ minute  
No load speed: 7.800 min  
Overall length: 460mm  
Net weight: 4.7kg  
Vibration emission: [ah] 9.3m/s<sup>2</sup>  
Sound level: [Lwa] 90.8dB  
Power source: Unleaded fuel only

## MATERIAL SPECIFICATION:

Plastic casing and fuel tank  
Solid state ignition system  
EPDM Rubber inflation and suction nozzle

## OPERATING AND DESIGN STANDARDS:

Conforms to 2006/42/EC and 2000/14/EC  
Manufactured to EN15503  
Vibration determined to EN60745  
Weight according to EPTA 01/2003

## INSPECTION ROUTINE:

### Before each work session

Always be sure the engine is cool before attempting any inspections.  
Remove oil cap. Wipe oil indicator. Reinstall oil cap and remove. Confirm if oil is between upper and lower indicator. Top up if required with SAE 10W-30 oil only.  
Visually inspect casing and fuel tank for damage.

## MAINTENANCE SCHEDULE:

### Every 3 months

Always be sure the engine is cool before attempting any maintenance.



Wipe down casing and engine covers.  
Keep all parts clean and dust free. Do not use any solvents to clean only a dry rag.  
Remove all engine oil and replace with new. Only use SAE 10W-30 oil.  
Remove air filter, blow clean and reinstall. Replace if damaged.  
Remove engine spark plug. Clean with a wire brush. Reinstall engine spark plug. Replace if damaged.  
Spare parts available from Sayfa Systems.

## TRAINING REQUIREMENTS:

All operatives must be trained and wear appropriate PPE including gloves, goggles and ear protection.  
Sayfa Systems offer product training and operator certification.